






**TECHNICAL FEATURES OF INJECTORS FOR THE APPLICATION: HEAVY DUTY MULTI POINT&SINGLE POINT INJ. ; BUS, TRUCK, INDUSTRIAL ENGINE, GENERATORS  
(STATIONARY ENGINE)**

<b>PRODUCT TYPE</b>	<b>IG6 POTOMAC</b>		<b>IG6 TAURUSII</b>		<b>IG7 DAKOTA HP</b>	<b>IG4 DAKOTA "8L"</b>	
							
<b>FEATURES</b>	<i>Coil Resistance 1,5 Ohm</i>	<i>Coil Resistance 4,7 Ohm</i>	<i>Coil Resistance 2 Ohm</i>	<i>Coil Resistance 4,7 Ohm</i>	<i>2 Ohm</i>	<i>Coil Resistance 1 Ohm</i>	<i>Coil Resistance 4,7 Ohm</i>
<b>FUEL TYPE ON APPLICATION</b>	CNG		CNG		CNG	CNG	
<b>OPENING TIME (ms)</b>	2,15	2,1	2,4	2,4	1,9	2,7	
<b>MAX FLOW RATE</b>	15,2 kg/h	15,2 kg/h	18 kg/h x Cyl.	18 kg/h x Cyl.	17 kg/h x Cyl.	31,1 kg /h x Cyl.	
<b>N° OF CYLINDER</b>	1 single		3,4,5 and 6		2,3 and 4	1 single	
<b>DURABILITY</b>	500 million		500 million		500 million	500 million	
<b>MAX PRESSURE RANGE</b>	5	9	5	9	7	8	