





TECHNICAL FEATURES OF INJECTORS FOR THE APPLICATION: OEM, 0 KM, PASSENCAR VEHICLES, BI-FUEL OR MONOFUEL, LIGHT COMMERCIAL VEHICLES, DIRECT INJECTION ENGINE

PRODUCT TYPE	IG7 DAKOTA			IG4 DAKOTA OEM			IG4 DAKOTA AFTER MARKET		
									
	<i>LP VERSION</i>		<i>LHF VERSION</i>	<i>LP</i>		<i>LHF</i>	<i>LP</i>		<i>LHF</i>
FEATURES	<i>1 OHM / 2 OHM</i>		<i>2 OHM</i>	<i>1 OHM / 2 OHM</i>		<i>2 OHM</i>	<i>1 OHM / 2 OHM</i>		<i>2 OHM</i>
FUEL TYPE ON APPLICATION	LPG - CNG			LPG - CNG			LPG - CNG		
OPENING TIME (ms)	1,4	1,7	1,8	1,4	1,7	1,8	1,4	1,7	1,8
MAX POWER FOR LPG 1 BAR (kW)	28/Cyl.	33/Cyl.	43/Cyl.	28/Cyl.	33/Cyl.	43/Cyl.	28/Cyl.	33/Cyl.	43/Cyl.
MAX POWER FOR CNG 2 BAR (kW)	25/Cyl	29/Cyl.	38/Cyl.	25/Cyl.	29/Cyl.	38/Cyl.	25/Cyl.	29/Cyl.	38/Cyl.
DURABILITY	1 Billion		700 Million	1 Billion		700 Million	1 Billion		700 Million